COFFRETS « BRIS DE GLACE » Exe ET Exd

ENCLOSURES « MANUAL CALL POINT » Exe AND Exd





CARACTERISTIQUES TECHNIQUES

Attestation d'examen CE de type Exe: LCIE 11 ATEX 3062X
Type homologué : BAS-P
Zones : 1 et 2 (Gaz) – 21 et 22 (Poussières)
Groupe de gaz et de poussières : Ⓔx II 2 GD
Marquage : Exd e IIC T*Gb, Ex td IIIC T* Db
Degré de protection : IP65
Température ambiante : –20°C +40°C
Matière : Polyester fibre de verre chargé graphite RAL9011
Presse-étoupe : M20 Polyamide 8-13mm
Dimension :110x75x75mm
Fixations par 2 vis – Entraxes : 48x95mm

Attestation d'examen CE de type Exd : LCIE 03 ATEX 6146
Type homologué : DAS
Zones : 1 et 2 (Gaz) – 21 et 22 (Poussières)
Groupe de gaz et de poussières : Ⓔx II 2 GD
Marquage : Exd IIC T* Gb – Ex td IIIC T* Db
Degré de protection : IP65
Température ambiante : –20°C +40°C
Matière : Fonte Peinture Rouge
Presse-étoupe :M20 Laiton Nickelé 8.5-16mm
Dimension :129x129x75mm
Fixations par 2 vis – Entraxes : 80x75mm

DIRECTIVE EUROPEENNE

2014/34/UE Directive - ATEX

NORMES EUROPEENNES

EN 60079-0 Exigences Générales. (2012)
EN 60079-1 Enveloppes antidéflagrantes. (2007)
EN 60079-7 Protection par sécurité augmentée. (2007) (pour BAS-P)
EN 60079-31 Protection des poussières par enveloppes "t". (2009)

TECHNICAL CHARACTERISTICS

EC type examination certificate Exe : LCIE 11 ATEX 3062X
Type approved : BAS-P
Zones : 1 and 2 (Gas) – 21 and 22 (Dust)
Gas and dust group : Ⓔx II 2 GD
Marking : Exd e IIC T*Gb, Ex td IIIC T* Db
Degree of protection : IP65
Ambient temperature : –20°C +40°C
Material : Glassfibre-reinforced duroplastic Polyester, graphite added RAL9011
Cable Gland: M20 Polyamid 8-13mm
Size :110x75x75mm
Fixing by 2 Screws – Distances : 48x95mm

EC type examination certificate Exd : LCIE 03 ATEX 6146
Type approved : DAS
Zones : 1 and 2 (Gas) – 21 and 22 (Dust)
Gas and dust group : Ⓔx II 2 GD
Marking : Exd IIC T6 – Exd IIC T* Gb – Ex td IIIC T* Db
Degree of protection : IP65
Ambient temperature : –20°C +40°C
Material : Cast iron Painting red
Cable gland :M20 Laiton Nickelé 8.5-16mm
Size : 129x129x75mm
Fixing by 2 Screws – Distances : 80x75mm

EUROPEAN UNION DIRECTIVE

2014/34/UE Directive - ATEX

EUROPEAN UNION RULES

EN 60079-0 Explosive atmospheres.(2012)
EN 60079-1 Flameproof enclosures.(2007)
EN 60079-7 Increased security protection. (2007) (for BAS-P)
EN 60079-31 Protection dust by enclosures "t". (2009)