PRESSE-ETOUPES
CABLE GLANDS

Ex II 2 GD Exdb,eb,tb IP66 / IP68
INERIS 12 ATEX 0032X
IECEx INE 12.0025X

ADE1F - Presse étoupe pour câble non armé, laiton nickelé
ADE1F - Cable Gland for unarmoured cable, nickel plated brass



ISO				NPT			
Réf.	Diam.	N°	Ø de serrage externe	Réf.	Diam.	N°	Ø de serrage externe
CAP806604V1	M20	06	10-16mm	CAP808604V1	½	06	10-15,5mm
CAP806674V1	M20	04	4,5-8,5mm	CAP808674V1	½	04	4,5-8,5mm
CAP806694V1	M20	05	7-12mm	CAP808694V1	½	05	7-12mm
CAP806704V1	M25	07	13,5-20,5mm	CAP808704V1	¾	07	13,5-20,5mm
CAP806774V1	M25	05	7-12mm	CAP808774V1	¾	05	7-12mm
CAP806794V1	M25	06	10-16mm	CAP808794V1	¾	06	10-16mm
CAP806704V1	M25	07	13,5-20,5mm	CAP808704V1	¾	07	13,5-20,5mm
CAP806804V1	M32	08	18-27,5mm	CAP808804V1	1	08	18-26mm
CAP806904V1	M40	09	23-34mm	CAP808904V1	1 ¼	09	23-34mm
CAP807004V1	M50	10	29-41mm	CAP809004V1	1 ½	10	29-41mm
CAP807084V1	M50	11	35-45mm	CAP809294V1	1 ½	11	35-48mm
CAP807204V1	M63	12	42-56mm	CAP809204V1	2	12	42-53mm

ADE4F - Presse étoupe pour câble armé ou blindé Laiton nickelé
ADE4F - Cable Gland for armoured braided cable nickel plated brass



ISO					NPT				
Réf.	Diam.	N°	Ø de serrage externe	Ø de serrage interne	Réf.	Diam.	N°	Ø de serrage externe	Ø de serrage interne
CAP846604V1	M20	07	13,5-21mm	10-15,5mm	CAP848604V1	½	07	13,5-21mm	10-15,5mm
CAP846674V1	M20	05	7-12mm	4,5-8mm	CAP848674V1	½	05	7-12mm	4,5-8mm
CAP846694V1	M20	06	10-16mm	7-12mm	CAP848694V1	½	06	10-16mm	7-12mm
CAP846704V1	M25	08	18-27,5mm	13,5-20,5mm	CAP848704V1	¾	08	18-27,5mm	13,5-20,5mm
CAP846774V1	M25	06	10-16mm	7-12mm	CAP848774V1	¾	06	10-16mm	7-12mm
CAP846794V1	M25	07	13,5-21mm	10-15,5mm	CAP848794V1	¾	07	13,5-21mm	10-15,5mm
CAP846804V1	M32	09	23-34mm	18-26mm	CAP848804V1	1	09	23-34mm	18-26mm
CAP846894V1	M32	08	18-27,5mm	13,5-21mm	CAP848894V1	1	08	18-27,5mm	13,5-21mm
CAP846904V1	M40	10	29-41mm	23-34mm	CAP848904V1	1 ¼	10	29-41mm	23-34mm
CAP846994V1	M40	09	23-34mm	18-27,5mm	CAP848994V1	1 ¼	09	23-34mm	18-27,5mm
CAP847004V1	M50	11	35-48mm	29-41mm	CAP849004V1	1 ½	11	35-48mm	29-41mm
CAP847094V1	M50	10	29-41mm	23-34mm	CAP849094V1	1 ½	10	29-41mm	23-34mm

CARACTERISTIQUES TECHNIQUES
Type homologué : ADE1F & 4F
Zones : 1 et 2 (Gaz) – 21 et 22 (Poussières)
Groupe de gaz et de poussières : Ⓔx II 2 GD
Marquage : Ex db,eb,nRc,tb
Degré de protection: jusqu'à IP68 selon conditions. Nous consulter.
Matière: Laiton nickelé

SUR DEMANDE
Autres matières (Inox 316L, Bronze, Aluminium) & tailles, nous consulter

TECHNICAL CHARACTERISTICS
Type approved : ADE1F & 4F
Zones : 1 and 2 (Gas) – 21 and 22 (Dust)
Gas and dust group : Ⓔx II 2 GD
Marking : Ex db,eb,nRc,tb
Degree of protection: up to IP68 depending on conditions. Consult us.
Material: nickel plated brass

ON REQUEST
Other materials (316 Stainless steel, bronze and aluminium) and size, please contact us